

**IQMAX<sup>®</sup>**

**H3**



**CROSS FLOW  
AIR CURTAIN**



***Fresh Air Fresh Life!***



Metal casing



Adjustable air  
deflector



High efficient  
motor



Quiet wind  
wheel



Remote  
control



Magnetic  
door

Optional:

# Model H3

## Cross Flow



Metal casing



Adjustable air deflector



High efficient motor



Quiet wind wheel

### Optional :



Remote control



Magnetic door

### Warranty one year for product ,Warranty five years for motor

★ Utility model patent No.: CN201821756562.9

- **Fashionable appearance design:** Applying quadrate hole punching design, fashionable looks, serializing together with H5 and H7.
- **Improved air duct design:** convenient for assembling, bringing powerful, smooth and even air flow, making a great air curtain effect, and the installing high will be roundly 0.3m higher than competitor.
- **Unique segmented splice panel design:** front panel splicing with upper and lower plate, can be multi-matching as: white + black, all black, all white, etc.
- **High efficiency motor:** Adopting self-made motor, powerful, low noise, more reliable.
- **Multi-control ways:** With remote control receiver and manual key design, the operation is more convenient, standard two speeds, three speeds for option, which is suitable for a variety of places.
- **Intelligent magnetic door switch (Optional):** Realize humanized control of door opening and closing, greatly reduce indoor air outflow and save energy.
- **Double voltage (For option):** Motor can be optional for 110V/220V, suitable for some area with double voltage like Taiwan, South America.

### Parameters

Model	Voltage/ Frequency (V/Hz)	Input Power (W)	Air Velocity (m/s)	Air Volume (m <sup>3</sup> /h)	Noise (dB)	Diameter Of Impeller (mm)	Net Weight (KG)	Gross Weight (KG)	Unit Size (mm)	The Installation Height (m)
IM-CMR09	220-240V/50Hz	100	10-11	1550	≤45	100	9.1	10.6	910×178×176	2.3-3
IM-CMR10	220-240V/50Hz	115	10-11	1720	≤45	100	9.8	11.5	1005×178×176	2.3-3
IM-CMR12	220-240V/50Hz	135	10-11	2130	≤46	100	11.5	13.5	1205×178×176	2.3-3
IM-CMR15	220-240V/50Hz	150	10-11	2650	≤48	100	14.3	16.8	1500×178×176	2.3-3
IM-CMR18	220-240V/50Hz	180	10-11	3200	≤50	100	17.5	20.3	1795×178×176	2.3-3
IM-CMR20	220-240V/50Hz	185	10-11	3550	≤52	100	18.8	22.0	2000×178×176	2.3-3

Back diagram



Vertical view

